

17. (Amended) The reflection type liquid crystal display device according to Claim 15, wherein the existence probability along said first direction has one peak in a  $15^{\circ} - 19^{\circ}$  range, and the existence probability along said second direction has a peak in a  $15^{\circ} - 19^{\circ}$  range and  $0^{\circ} - 14^{\circ}$  range respectively.

18. (Amended) The reflection type liquid crystal display device according to Claim 15, wherein the existence probability along said second direction has a peak in a first angle range and a second angle range in a first area, and the existence probability along said second direction has a peak in said first angle range and a third angle range in a second area in each pixel area of the display face.

27. (Amended) The reflection type liquid crystal display device according to Claim 24 or Claim 26, wherein a direction of refractive index anisotropy of said liquid crystal layer changes according to the electric field to be applied, a transparent prism-shaped undulated layer is disposed between one of said transparent substrates and said liquid crystal layer, and a refractive index of said undulated layer matches with one refractive index of the liquid crystal layer.

28. (Amended) The reflection type liquid crystal display device according to Claim 24 or Claim 26, wherein said transparent electrodes are separated into a plurality of

A<sup>2</sup>  
concl'd

parts and voltage is selectively applied to a separated transparent electrode, so as to adjust the degree of light scattering of said liquid crystal layer.

32. (Amended) The method of manufacturing a reflection type liquid crystal display device according to Claim 30, wherein the exposure time is adjusted to expose said resin layer using an arbitrary mask pattern when the distribution of the thermal deformation characteristics of said resin layer is adjusted, so that the film thickness of said resin layer is distributed and said undulation shape of said resin layer is controlled.

33. (Amended) The method of manufacturing a reflection type liquid crystal display device according to Claim 30, wherein when at least one type of composing elements to be disposed on the surface of said substrate is formed, the distribution of thermal deformation characteristics of said resin layer is adjusted and said undulation shape of said resin layer is controlled using said composing elements by setting at least one of number, shape and arrangement of said composing elements to a desired value.

36. (Amended) The method of manufacturing a reflection type liquid crystal display device according to Claim 34, wherein said part is formed by forming a resin layer having a predetermined shape with different thermal deformation characteristics in said resin layer.

PA  
concl'd  
Sno

37. (Amended)

The method of manufacturing a reflection type liquid crystal display device according to Claim 34, wherein said part having different thermal deformation characteristics is formed by performing partial processing on said resin layer.

40. (Amended)

The method of manufacturing a reflection type liquid crystal display device according to Claim 38, further comprising a fourth step of performing heat treatment to said resin layer before said first step.

41. (Amended)

The method of manufacturing a reflection type liquid crystal display device according to Claim 38, wherein said resin layer is patterned before said first step.

42. (Amended)

The method of manufacturing a reflection type liquid crystal display device according to Claim 38, wherein an undulation pattern is formed on said substrate before said first step.

45. (Amended)

The reflection type liquid crystal display device according to Claim 43, wherein at least one of number, shape and arrangement of comprising elements disposed on the surface of said substrate is set to a desired value and an area having a

A6  
concl'd

different distribution of said undulation is formed corresponding to said setting.

A7

48. (Amended) The reflection type liquid crystal display device according to Claim 45, wherein the average inclination angle of said undulation of said resin layer is a value between  $8^{\circ}$  and  $13^{\circ}$ .

10054309-011802  
A8

51. (Amended) The reflection type liquid crystal display device according to Claim 49, wherein said part is comprised of particles having different thermal deformation characteristics in the resin layer.

52. (Amended) The reflection type liquid crystal display device according to Claim 49, wherein said part is comprised of another resin layer having different thermal deformation characteristics layered in said resin layer.

53. (Amended) The reflection type liquid crystal display device according to Claim 49, wherein said part is comprised of another resin layer having different thermal deformation characteristics formed into a predetermined shape in said resin layer.

A9

63. (Amended) The reflection type liquid crystal display device according to Claim 59 or Claim 60, wherein an optical element to improve directivity of light is

ADD  
CONC'D

disposed in said light guiding plate.

69. (Amended) The illumination device according to Claim 65, wherein

A10  
said low refractive index layer and said transparent conductive film are formed on said light guiding plate side face of the transparent element disposed at the observer side of said light guiding plate, and said low refractive index layer and said light guiding plate contact each other at least in a part of the area.

A1  
73. (Amended) The illumination device according to Claim 71, wherein

an optical element to improve a directivity of light is disposed in said light guiding plate.